Fate Report for Case # P-17-0023

Fate

Summary Statement

```
Fate P-17-0023
 Summary
Statement: FATE:
            Solid with MP = 95-97 °C (M)
            \log Kow = -0.90 (E)
            > 10 \text{ g/L at } 25 \text{ °C (E)}
            VP = 4.4E-2 \text{ torr at } 25 \text{ }^{\circ}\text{C (E)}
            BP = 209 \, ^{\circ}C
            (E)
            H = 1.15E-6 (E)
            \log Koc = 0.97 (E)
            \log \text{ Fish BCF} = 0.50 (3)
            log Fish BAF = -0.05 (1) (E)
            POTW removal (%) = 0-25 via
            possible biodeg
            Time for complete ultimate aerobic biodeg = wk
            Sorption to soils/sediments = low
            Volatilization half-life from a
            standard river = 570 \text{ hrs}
            Volatilization half-life from a standard lake
            = 260 da
            Atmospheric Oxidation Half-life = 120 hr via OH radical
            PBT Potential: P3B1
            *CEB FATE: Migration to ground water = rapid
            Overall wastewater treatment removal is 0-25% based analogous
            chemicals.
            Sorption to sludge is low based on analogous chemicals.
            Air Stripping (Volatilization to air) is low based on analogous
            chemicals and the estimated vapor pressure.
            Removal by biodegradation
            in wastewater treatment is negligible to moderate based on analogous
            chemicals and BIOWIN model estimates.
            The aerobic aquatic
            biodegradation half-life is weeks based on analogous chemicals.
```

The

anaerobic aquatic biodegradation half-life is months to greater than months based on the aerobic biodegradation half-life. The anaerobic biodegradation half-life is projected to be greater or equal to the aerobic biodegradation half-life.

Sorption to soil and

sediment is low based on PCKOC model estimates and analogous chemicals.

Migration to groundwater is rapid based on the estimated water solubility and analogous chemicals.

PMN Material:

High Persistence

(P3) is based on the anaerobic biodegradation half-life.

Low

Bioaccumulation potential (B1) is based on analogous chemicals.

CBI:

Fate Placeholder,

Assessor: Legacy

SMILES:

Physical Properties

Property	Measured/Calculated	EPI
	Value	
Molecular Form:	C2 H4	C2 H4 O4
	O4 S	S1
Molecular Wt.:	124.12	124.11
%		
< 500:		
%		
< 1000:		

Property	Measured Value	Method	Estimated Value	Method	EPI
	95.00 - 97.00	Exp.			95.00
Point:					
Boiling			209	EPI	209.15
Point:					
BP			@760		@760
Pressure:			_		
Vapor			0.043	EPI	4.41e-002
Pressure:					

Property	Measured	Method	Estimated	Method	EPI
	Value		Value		
Water			407	EPI	
Solubility:					
Log P:			-0.90		
Log					-0.90
Kow:					
Log Koc:					0.97
Log BCF:					3.1600
Henry's					1.15e-006
Law:					

рН: рН Comment:

Fate Analysis

Hydrolysis (t1/2, da):		Volatilization (t1/2) - River (hr):	568.3000	Volatilization (t1/2) - Lake (da):	262.2100
Atm Ox Potential (t1/2)OH (hr):	124.6900	Atm Ox Potential (t1/2)O3 (hr):		Atm Ox Potential (t1/2) Total (hr):	124.6900
MITI Linear:		MITI NonLinear:			
Biodeg Linear:	0.6900	Biodeg NonLinear:	0.7800		
Biodeg Survey ult:	WK	Biodeg Survey Prim:	DA-WK		
STP (% removal) Total:	1.9100	STP (% removal) Biodeg:	0.0900		
STP (% removal) Ads:	1.7500	STP (% removal) Air:	0.0700		

Rationales

Removal in	
Wastewater	
Treatment:	
Atmospheric	
Oxidation:	
Hydrolysis:	
Photolysis:	

Aerobic	
Biodegradation:	
Anaerobic	
Biodegradation:	
Sorption	
to Soil and	
Sediment:	
Migration to	
Groundwater:	
Persistence - Air:	
Persistence	
- Water:	
Volatilization	
from Water:	
Soil:	
Sediment:	
Other:	
Standard:	
Bioaccumulation:	

PBT Ratings

Persistence	Bioaccumulation	Toxicity	PBT Comments
3	1	2	

Exposure-Based Testing

Exposure-Based	
Testing:	

Fate Ratings

Removal in WWT/POTW

(Overall):

Removal in 0-25 WWT/POTW (Overall):

Condition	Rating		Rating Description			Comment
	Values	1	2	3	4	
WWT/POTW Sorption:	1	Low	Moderate	Strong	V. Strong	
	3	Extensive	Moderate	Low	Negligible	

Condition	Rating		Rating De	escription		Comment
	Values	1	2	3	4	
WWT/POTW						
Stripping:						
Biodegradation	3-4	Unknown	High	Moderate	Negligible	
Removal:						
Biodegradation		Unknown	Complete	Partial	_	
Destruction:						
Aerobic	2	<=	Weeks	Months	>	
Biodeg Ult:		Days			Months	
Aerobic Biodeg		<= Days	Weeks	Months	>	
Prim:					Months	
Anaerobic	3-4	<=	Weeks	Months	>	
Biodeg		Days			Months	
Ult:			*** 1	3.6 (1	_	
Anaerobic		<= Days	Weeks	Months	> Mantha	
Biodeg Prim:					Months	
Hydrolysis (t1/2		<=	Hours	Days	>=	
at pH		Minutes	Hours	Days	Months	
7,25C) A:		williates			Wionins	
Hydrolysis (t1/2		<=	Hours	Days	>=	
at pH		Minutes	Hours	Duys	Months	
7,25C) B:		111111111111111111111111111111111111111			111011111	
Sorption to	4	V.	Strong	Moderate	Low	
Soils/Sediments:		Strong	S			
Migration to	4	Negligible	Slow	Moderate	Rapid	
Ground Water:		2 2			1	
Photolysis A,		Negligible	Slow	Moderate	Rapid	
Direct:		- -			-	
Photolysis B,		Negligible	Slow	Moderate	Rapid	
Indirect:		_			-	
Atmospheric Ox		Negligible	Slow	Moderate	Rapid	
A, OH:						
Atmospheric Ox		Negligible	Slow	Moderate	Rapid	
B, O3:						

Bio

Comments:

Bio Fish log BAF = -0.05 **Comments:** (1).

Fate

Comments:

Fate Overall wastewater

Comments: treatment removal is 0-25% based analogous chemicals.

Sorption to

sludge is low based on analogous chemicals.

Air Stripping

(Volatilization to air) is low based on analogous chemicals and the estimated vapor pressure.

Removal by biodegradation in wastewater

treatment is negligible to moderate based on analogous chemicals and BIOWIN model estimates.

The aerobic aquatic biodegradation half-life

is weeks based on analogous chemicals.

The anaerobic aquatic

biodegradation half-life is months to greater than months based on the aerobic biodegradation half-life. The anaerobic biodegradation half-life is projected to be greater or equal to the aerobic biodegradation half-life.

Sorption to soil and sediment is low based on

PCKOC model estimates and analogous chemicals.

Migration to

groundwater is rapid based on the estimated water solubility and analogous chemicals.

PMN Material:

High Persistence (P3) is based on the anaerobic biodegradation half-life.

Low Bioaccumulation potential

(B1) is based on analogous chemicals.

Comments/Telephone Log

	8
Artifact	Update/Upload
	Time